


# JCH ball valve Type 745512

With male threads and PRK compression joints.  
Full bore. VA and SITAC approved.  
Prepared for AVK extensions spindle and street covers



Version 0116



JCH ball valve with male threads and compression joints.

#### Application:

Service valve for water supply and sewage.  
Suitable for drilling under pressure.

#### Test:

JCH 100% test

#### Accessories:

AVK extension spindles fixed lenght series 04/05.  
AVK extension spindles telescopic series 04/07.  
AVK street covers.


#### Material

Compression joint:	Acetal-plastic
Body:	DZR Brass CW625N
Spindle:	Stainless steel - AISI 303
Spindle and gasket	SEDI PTFE + O-rings of NBR rubber
Ball:	Stainless acid proof steel - AISI 316
Top gasket:	NBR O-rings
Top union:	DZR Brass CW602N
Gasket inside:	SEDI PTFE

# JCH ball valve Type 745512

## With 12mm # operating key.

### Prepared for AVK extension spindles and street covers.



Version 0116

Ball valve type 745512 is suitable as service valve for water supply and sewage.  
 The valve can be used for drilling under pressure because of the full bore version.  
 The valve is quick and easy to install and use.  
 The valve is made of the finest and best materials.



Order no.	LNS no.	R "	PE mm	DN mm	L1 mm mounted	L2 mm full lenght	H mm	NV1 mm spindle	NV2 mm valve	weight kg
745512-125	343-020-14-00	¾	25	20	98	114	133	16	40	1,25
745512-132	343-025-14-00	1	32	25	115	133	145	16	48	1,65
745512-140	343-032-14-00	1¼	40	32	130	148	156	16	55	2,24
745512-150	343-040-14-00	1½	50	40	146	166	160	16	69	3,35

**JCH A/S**

Karetmagervej 21 DK-7100 Vejle Tel. +45 75 85 84 08 Fax +45 75 85 80 82  
 CVR-nr. 87 56 20 18 | CVR-nr. DK 15 30 02 72