


JCH ball valve Type 745514

With PRK compression joints. Full bore
VA and SITAC approved.
Prepared for AVK extension spindles and
street covers.



Version 0116



Full bore ball valve with compression joints.

Applications:

Service valve for water supply and sewage.

Suitable for drilling under pressure

Test:

JCH 100% test

Accessories:

AVK extension spindles fixed length series 04/05.

AVK extension spindles telescopic series 04/07.

AVK street covers.


Materials

Compression joint:	Acetal-plastic
Body:	DZR brass CW625N
Spindle:	Stainless steel - AISI 303
Spindle gasket:	SEDI PTFE + O-rings of NBR rubber
Ball:	Stainless acidproof steel - AISI 316
Top gasket:	NBR O-rings
Top union:	DZR brass CW602N
Gasket inside:	SEDI PTFE

JCH ball valve Type 745514

With 12mm # operation key.

Prepared for AVK extension spindles and street covers.



Version 0116

Ball valve type 745514 is suitable as service valve in water supply and sewage.
 The valve can be used for drilling under pressure, because of the full bore version.
 The valve is quick and easy to install and use.
 The valve is made of the finest and best materials.



VVS nr.	LNS no.	PE mm	DN mm	L mm full lenght	H mm	NV1 mm spindle	NV2 mm PRK	Weight kg
745514-125	343-020-34-00	25	20	129	99	12	40	1,24
745514-132	343-025-34-00	32	25	156	104	12	48	1,74
745514-140	343-032-34-00	40	32	172	109	12	55	2,24
745514-150	343-040-34-00	50	40	197	119	12	69	3,55

JCH A/S

Karetmagervej 21 DK-7100 Vejle Tel. +45 75 85 84 08 Fax +45 75 85 80 82
 CVR-nr. 87 56 20 18 | CVR-nr. DK 15 30 02 72