


Ball valve Type 745515

With male and female threads. reduced.
Prepared for AVK extension spindle and
street cover.



Version 0116



Ball valve with male and female threads:

Application:

Service valve for water supply.

Test:

JCH 100% test

Accessories:

AVK extension spindles fixed lenght series 04/05.

AVK extension spindles telescopic series 04/07.

AVK street covers.


Material

Body:	DZR Brass CW625N
Spindle:	Stainless steel - AISI 303
Spindle-gasket:	SEDI PTFE + O-rings of NBR rubber
Ball:	Stainless acid proof steel - AISI 316
Top gasket:	NBR O-rings
Top union:	DZR Brass CW602N
Gasket inside:	SEDI PTFE

JCH ball valve Type 745515

With 12mm # operating key.

Prepared for AVK extension spindles and street covers.



Version 0116

JCH ballvalve type 745515 is applicable as stopvalve in watersupplys.
The pipeconnections gives many diffrent opportunities, ballvalve type 745515 is
quikly and easily to install and use, made of the finest and best materials.



Order no.	LNS no.	DN	L1 mm mounted	L2 mm full lenght	H mm	NV1 mm spindle	NV2 mm valve	weight kg
745515-006	343-015-44-00	15	61	75	96		32	0,95
745515-108	343-020-44-00	20	79	95	99	12	39	1,25
745515-110	343-025-44-00	25	89	107	104	12	42	1,65
745515-111	343-032-44-00	32	100	120	109	12	56	1,95
745515-112	343-040-44-00	40	106	128	119	12	70	2,95

JCH A/S

Karetmagervej 21 DK-7100 Vejle Tel. +45 75 85 84 08 Fax +45 75 85 80 82
CVR-nr. 87 56 20 18 | CVR-nr. DK 15 30 02 72