


JCH ball valve Type 745517

With female threads. Reduced bore.
Prepared for AVK extension spindles and street covers.



Version 0116



Reduced bore ball valve with female threads:

Applications:

Service valve for water supply and sewage.

Test:

JCH 100% test

Accessories:

AVK extension spindles fixed length series 04/05.

AVK extension spindles telescopic series 04/07.

AVK street covers.


Material

Body:	DZR Brass CW625N
Pipe coupling:	DZR Brass CW625N
Spindle:	Stainless steel - AISI 303
Spindle-gasket:	SEDI PTFE + O-rings of NBR rubber
Ball:	stainless acid proof steel - AISI 316
Top gasket:	NBR O-rings
Top union:	DZR Brass CW602N
Gasket inside:	SEDI PTFE

JCH ball valve Type 745517

with 12mm # opration key.

Prepared for AVK extension spindles and street covers.



Version 0116

Service valve for water supply and sewage.



Order no.	LNS no.	RP “	DN mm	L mm	H mm	NV1 mm spindle	NV2 mm Valve	weight kg
745517-108	343-020-54-00	1	20	82	99	12	39	1,04
745517-110	343-025-54-00	1¼	25	97	104	12	42	1,45
745517-111	343-032-54-00	1½	32	107	109	12	56	1,75
745517-112	343-040-54-00	2	40	117	119	12	70	2,65

JCH A/S

Karetmagervej 21 DK-7100 Vejle Tel. +45 75 85 84 08 Fax +45 75 85 80 82
 CVR-nr. 87 56 20 18 | CVR-nr. DK 15 30 02 72