


JCH ball valve Type 745512D with drain.

Prevents frost damage.
With male threads and PRK compression joints.
Full bore. Prepared for AVK extensions spindle and street covers



Version 0116



JCH ball valve with male threats and compression joints.

Application:

Service valve for water supply.

Suitable for drilling under pressure.

Suitable for drainage of water in house installations (summer cottage), to prevent frost damage.

Test:

JCH 100% test

Accessories:

AVK extension spindles fixed lenght series 04/05.

AVK extension spindles telescopic series 04/07.

AVK street covers.


Material

Compression joint:	Acetal-plastic
Body:	DZR Brass CW625N
Spindle:	Stainless steel - AISI 303
Spindle gasket	SEDI PTFE + O-rings of NBR rubber
Ball:	Stainless acid proof steel - AISI 316
Top gasket:	NBR O-rings
Top union:	DZR Brass CW602N
Gasket inside:	SEDI PTFE

JCH ball valve Type 745512D.

With 12mm # operating key.

Prepared for AVK extension spindles and street covers.



Version 0116

Service valve for water supply.
 Suitable for drilling under pressure.
 Suitable for drainage of water in house installations (summer cottage), to prevent frost damage.



Order no.	LNS no.	R "	PE mm	DN mm	L1 mm mounted	L2 mm full lenght	H mm	NV1 mm spindle	NV2 mm valve	weight kg
745512-332	343-025-14-10	1	32	25	115	133	145	16	48	1,65
745512-340	343-032-14-10	1¼	40	32	130	148	156	16	55	2,24
745512-350	343-040-14-10	1½	50	40	146	166	160	16	69	3,35

JCH A/S

Karetmagervej 21 DK-7100 Vejle Tel. +45 75 85 84 08 Fax +45 75 85 80 82
 CVR-nr. 87 56 20 18 | CVR-nr. DK 15 30 02 72