


JCH ball valve Type 745514D with drain.

Prevents frost damage.
With PRK compression joints.
Prepared for AVK extension spindles.



Version 0116



Ball valve with drain

Applications:

Service valve for water supply.

Suitable for drilling under pressure.

Suitable for drainage of water in house installations (summer cottage), to prevent frost damage.

Test:

JCH 100% test

Accessories:


AVK extension spindles, fixed length series 04/05.

AVK extension spindles, telescopic series 04/07.

Materials

Compression joint:	Acetal-plastic
Body:	DZR brass CW625N
Spindle:	Stainless steel - AISI 303
Spindle gasket:	SEDI PTFE + O-rings of NBR rubber
Ball:	Stainless acidproof steel - AISI 316
Top gasket:	NBR O-rings
Top union:	DZR brass CW602N
Gasket inside:	SEDI PTFE

**JCH ball valve Type 745514D with drain.
With 12mm # operation key.
Prepared for AVK extension spindles.**



Version 0116

Service valve for water supply.
Suitable for drilling under pressure.
Suitable for drainage of water in house installations (summer cottage), to prevent frost damage.



Order no.	LNS no.	PE mm	DN mm	L mm	H mm	NV1 mm spindle	NV2 mm body	Weight kg
745514-332	343-025-34-10	32	25	156	66	12	48	1,4
745514-340	343-032-34-10	40	32	172	71	12	55	1,9
745514-350	343-040-34-10	50	40	197	81	12	69	3,2

JCH A/S

Karetmagervej 21 DK-7100 Vejle Tel. +45 75 85 84 08 Fax +45 75 85 80 82
CVR-nr. 87 56 20 18 | CVR-nr. DK 15 30 02 72