


JCH ball valve Type 745515D with drain

Prevents frost damage.
With male and female threads. Reduced bore.
Prepared for AVK extension spindles and street covers.



Version 0116



Reduced bore ball valve with male and female threads:

Applications:

Service valve for water supply.

Suitable for drainage of water in house installations
(summer cottage), to prevent frost damage.

Test:

JCH 100% test

Accessories:

AVK extension spindles fixed length series 04/05.

AVK extension spindles telescopic series 04/07.

AVK street covers.


Materiale

Body:	DZR Brass CW625N
Spindle:	Stainless steel - AISI 303
Spindle-gasket:	SEDI PTFE + O-rings of NBR rubber
Ball:	Stainless acid proof steel - AISI 316
Top gasket:	NBR O-rings
Top union:	DZR Brass CW602N
Gasket inside:	SEDI PTFE

JCH ball valve Type 745515D

With 12mm # operation key.

Prepared for AVK extension spindles and street covers.



Version 0116

Service valve for water supply.
Suitable for drainage of water in house installations (summer cottage), to prevent frost damage.



Oder no.	LNS no.	R “	DN mm	L1 mm Mounted	L2 mm full length	H mm	NV1 mm Spindle	NV2 mm Valve	weight kg
745515-110D	343-025-44-10	1¼”	25	89	107	104	12	42	1,65
745515-111D	343-032-44-10	1½”	32	100	120	109	12	56	1,95
745515-112D	343-040-44-10	2”	40	106	128	119	12	70	2,95

JCH A/S

Karetmagervej 21 DK-7100 Vejle Tel. +45 75 85 84 08 Fax +45 75 85 80 82
CVR-nr. 87 56 20 18 | CVR-nr. DK 15 30 02 72